DECLARATION OF PERFORMANCE № 30/3/2017

- 1. Unique identification code of the product-type: <u>30</u>
- 2. Type, batch or serial number or any other element allowing identification of construction product:

 Laminated safety glass (3-0,38-3, 3-0,76-3, 4-0,38-4, 4-0,76-4, 5-0,38-5, 5-0,76-5, 6-0,38-6, 6-0,76-6),
 output according to EN 14449 Glass in building —Laminated glass and laminated safety glass.

 Evaluation of conformity/product standard. EN ISO 12543-2 Glass in building. Laminated glass and laminated safety glass-Part 2: Laminated safety glass
- 3. Intended use or use of the construction product, in accordance with the applicable harmonised technical specification:

For application in buildings and constructions accoding to EN 14449 Glass in building – Laminated glass and laminated safety glass. Evaluation of conformity/product standard

- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer: <u>JSC «Gomelglass»</u>, <u>Belarus</u>, <u>247045</u>, <u>Gomel, Mihail Lomonosov str.</u>, <u>25</u>
- 5. Name and contact address of the authorised representative: Schollglas Polska Sp.zo.o. UI. Zakladowa 39, 39-400 Tarnobrzeg, Poland
- 6. System or system of assessment and verification of constancy of of the conctraction product:

System «3». Declaration of the performance of the essential characteristics of the construction product by the manufacturer:

- (a) the manufacturer shall carry out factory production control;
- (b) the notified testing laboratory shall carry out determination of the product-type on the basis of type testing, type calculation, tabulated values or descriptive documentation of the product
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standart:

Division of Glass and Building Materials in Cracow Institute of Ceramics and Building Materials

performed testing under system «3»

(description of the third party)

and issued Test Report No 008 FW.14.N date 09.09.2014

(certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports - as relevant)

- 8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: --
- 9. Declarated performance

Essential caracteristics		Performance	Harmonised technical specification
Resistance to fire	W. 173	NPD	_
Reaction to fire	100	NPD	-
External fire performance	7	NPD	
Bullet resistanse		NPD	-
Explosion resistance		NPD	-
Burglar resistance		NPD	

Essential caracteristics	Performance	Harmonised
		technical
		specification
Pendulum body impact resistance for each thickness		EN 12600
3-0,38-3	2(B)2	EN 12000
4-0,38-4	2(B)2 2(B)2	
5-0,38-5		
6-0,38-6	2(B)2	
3-0,76-3	1(B)1	
	2(B)2	
4-0,76-4	1(B)1	
5-0,76-5	1(B)1	
6-0,76-6	1(B)1	
Resistance against sudden temperature changes and	40 K	EN 572 1
temperature differentials	10 10	EN 572-1
Wind, snow, permanent and imposed load resistance	NPD	
Direct airborne sound insulation (4-0,76-4)	34-1-3 dB	EN 12758
Thermal properties	NPD	EN 12/38
Radiation properties:	11110	EN 410
Light transmittance / reflectance for each thickness		EN 410
3-0,38-3	0,89/0,11	
3-0,76-3	0,90/0,11	
4-0,38-4	0,88/0,10	
4-0,76-4	0,89/0,11	
5-0,38-5	0,88/0,10	
5-0,76-5	0,88/0,10	
6-0,38-6	0,87/0,10	
6-0,76-6	0,88/0,10	
Solar direct transmittance / Solar direct reflectance	0,00.0,20	TENI 410
for each thickness		EN 410
3-0,38-3	0,78/0,11	
3-0,76-3	0,77/0,11	
4-0,38-4	0,74/0,10	
4-0,76-4	0,73/0,10	
5-0,38-5	0,73/0,10	
5-0,76-5	0,72/0,10	
5-0,38-6	0,70/0,09	
5-0,76-6	0,70/0,10	
Solar transmittance for each thickness	0,70,0,10	TIN 440
1-0,38-3	0,80	EN 410
3-0,76-3	1 '	
-0,38-4	0,80	4
-0,76-4	0,78	*
i-0,38-5	0,77	
-0,76-5	0,77 0,76	
6-0,38-6	0,76	
6-0,76-6	0,75	
Durability		EN ICC 127
IDD. At D. C. D	matches	EN ISO 12543-2

«NPD» - No Performance Determined

10. The performance of the product identified in points 1 and 2 is in conformiti with the declared performance in point 9.

This declaration of performance is such times the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the marufacture:

Technical director JSC	C «Gomelglas»	A	Aleksandr Kamenev
(name and function)	70	18,07, XV142	
Gomel	07 *		
(place and date of issue)	TO METE TO METE		(signature)